



Adhesive recommendation for PURLINE ORGANIC FLOORING (for Canada only!)

General information:

- The subfloor must be prepared in accordance with VOB DIN 18365. The relevant data sheets, such as TKB data sheet no. 8 “Assessing and preparing subfloors for floor covering and engineered wood work” must be observed.
- In order to achieve the best wetting of the FleeceTEC backing, PURLINE floor coverings should be laid in the semi-wet bed of adhesive.
- Take up as much adhesive as possible as can be laid during the working time.
- Windmüller GmbH recommends an A2 toothing for the application of the adhesives. This recommendation may differ from the manufacturer's specifications.
- Press down straight after laying the covering in the bed of adhesive using a smoothing cork/ handled smoother and heavy roller (at least 50 kg).
- Only use adhesives that are
 - low on emissions,
 - solvent-free
 - and RAL UZ113 (Blue Angel) or EC1 certified.
- In rare cases, it is not possible to do without contact or reactive resin adhesive (high weight loads, strong sunshine, high temperatures etc.) If you have any questions about this, contact our hotline.
- It is recommended to work with all the necessary components (e.g. adhesive primer, fillers, adhesives etc.) from one system, i.e. from one manufacturer.
- Observe the specifications and processing guidelines of the adhesive and filler manufacturers.

Adhesive for installing PURLINE organic flooring rolls and planks

Manufacturer	Contact	Product
Kiesel Bauchemie GmbH u. Co.KG	www.kiesel.com	Okatmos star 100 Plus

It is essential to check before installation whether the adhesive is suitable for the intended application area and type of exposure. In case of questions or alternative solutions to adhesives, please contact the application technology department of the respective adhesive manufacturer.

With the publication of this adhesive recommendation (status 11/2019) all previous versions lose their validity.

If you have any questions, please contact:
Windmüller GmbH
Installation hotline: +49 (0) 52 37 – 609-530

Subject to technical modifications, status 11/2019

